



Search result: 1 of 1

(WO/1997/014075) LIGHT-TRANSMITTING MATERIAL, PLANAR LIGHT SOURCE DEVICE AND LIQUID CRYSTAL DISPLAY DEVICE

Biblio. Data	Description	Claims	National Phase	Notices	Documents
--------------	-------------	--------	----------------	---------	-----------



Latest bibliographic data on file with the International Bureau

Pub. No.: WO/1997/014075 International Application No.: PCT/J1996/002822
 Publication Date: 17.04.1997 International Filing Date: 27.09.1996
 Chapter 2 Demand Filed: 02.04.1997

IPC: F21V 8/00 (2006.01), G02F 1/13357 (2006.01), G02B 6/00 (2006.01), G02F 1/1335 (2006.01)

Applicants: IBM JAPAN LTD. [JP/JP]; 2-12, Reppongi 3-chome, Minato-ku, Tokyo 106 (JP) (All Except US).
 MAMIYA, Johji [JP/JP]; (JP) (US Only).
 SEKISUI KAGAKU KOGYO KABUSHIKI KAISHA [JP/JP]; 4-4, Nishitenma 2-chome, Kita-ku, Osaka-shi, Osaka-fu 530 (JP) (All Except US).
 SUZUKI, Masaru [JP/JP]; (JP) (US Only).
 TANASE, Hiroshi [JP/JP]; (JP) (US Only).
 NAKAMURA, Kozo [JP/JP]; (JP) (US Only).
 HATAZAWA, Tsuyonobu [JP/JP]; (JP) (US Only).
 WATANABE, Takashi [JP/JP]; (JP) (US Only).
 HAYASHI, Hideki [JP/JP]; (JP) (US Only).

Inventors: MAMIYA, Johji; (JP).
 SUZUKI, Masaru; (JP).
 TANASE, Hiroshi; (JP).
 NAKAMURA, Kozo; (JP).
 HATAZAWA, Tsuyonobu; (JP).
 WATANABE, Takashi; (JP).
 HAYASHI, Hideki; (JP).


Agents: GODA, Kiyoshi et al.; IBM Japan Ltd., Yamato Site, 1623-14, Shimotsuruma, Yamato-shi, Kanagawa-ken 242 (JP).
 YAMAMOTO, Jiro et al.; Tongu & Yamamoto International, Tokyo Tatemono Machida Building 2nd Floor, 1-16, Nakamachi 1-chome, Machida-shi, Tokyo 194 (JP).

Priority Data: 7/263945 12.10.1995 JP
 7/318922 07.12.1995 JP
 8/136997 30.05.1996 JP

Title: LIGHT-TRANSMITTING MATERIAL, PLANAR LIGHT SOURCE DEVICE AND LIQUID CRYSTAL DISPLAY DEVICE

Abstract: A light-transmitting material having extremely high light utilization efficiency and having diversified forms having a uniform in-plane luminance distribution, and an in-plane light source device for a liquid crystal display device using the light-transmitting material. This material has a first plane as an incidence surface of natural polarized light as incident light and a second plane different from the first plane, as an outgoing surface of specific polarized light generated by modulating natural polarized light, wherein interfaces of two kinds of materials having different refractive indices are arranged at angles $\{g(u)_z B\} \pm \{g(a)^*\}$ satisfying a polarizing angle condition with respect to a main travelling direction of incident light, at least two directions of the interface exist in one light conductor and the difference of the two kinds of materials having different refractive indices is 0.001 to 1.0. Generally, $g(u)_z B$ is about 45°.

The light-transmitting material further includes a first transparent member having a first refractive index and equipped with a plurality of rectangular equilateral triangle ridges on the first surface thereof and a second transparent member having a second refractive index and equipped with a plurality of downwardly rectangular equilateral triangle grooves in the second surface thereof, and the first and second surfaces come into contact with each other.



WORLD
INTELLECTUAL
PROPERTY
ORGANIZATION



IP SERVICES

NL, PT, SE).

Home IP Services PATENTSCOPE Patent Search